

www.strawblanket.com

S2000D Double Net Straw Blanket

Contents:	100% weed free straw
Netting:	Double Polypropylene with UV degrader Photodegradable with UV degrader additive
Thread:	Photodegradable with UV degrader additive
Standard Roll Size:	50 to 1000 sq yards/ 41.8 to 836 sq meters
Standard Width:	4,8 and 16 feet/ 1.22,2.44 and 4.88 meters
Functional Longevity*:	Up to 12 months
Best Use:	2:1 slopes, Medium-flow, roadways

S2000D is a fully Photodegradable with UV degrader additive blanket. The netting is made from Double Polypropylene with UV degrader. The thread is Photodegradable with UV degrader additive, while the filament of matrix is 100% weed free straw.

Blankets can be produced from 50 SY to 1,000 SY and be from 4 ft. to 16 ft. wide.

As described in Federal Highway Administration's Standard Specification FP-03 in Section 713.17 and as described by ECTC as a Type 2.D.

*Longevity dependent on geographical location as well as solar days.



Test Method Description	Standard Testing
Mass/Unit Area ASTM D 6475	8.3 oz/sq yd
Tensile Strength –MD ASTM D 6818	75 lbs/ft*
Tensile Strength –TD ASTM D 6818	75 lbs/ft*
Thickness ASTM D 6525	0.25+ inches*
Light Penetration ASTM D 6567	16%
Water Absorption ASTM D 1117, ECTC TASC 00197	386%
Elongation –MD ASTM D 6818	23.4%
Elongation –TD ASTM D 6818	26%
C Factor	<0.20@2:1*
Permissible Shear Stress	1.75 lbs/ft
Permissible rate of flow	6 ft/s*
<p>Enviroscape ECM certifies that the above criteria is met by this specified product and that it meets requirements as described in the Federal Highway Administration's Standard Specification FP-03 in Section 713.17 and as described by ECTC as a Type 2.D.</p> <p>*MARV-Minimum Average Roll Value. Actual manufactured MARV's meet or exceed above stated values.</p>	

This spec may also be downloaded at www.strawblanket.com/prod01.htm



Toll free: 888.550.1999
Phone: 419.594.3210
Fax: 419.594.3213

22700 St. Rt. 613
Oakwood, OH 45873
Email: Info@Strawblanket.com

Updated on 5-4-16

